



# Woodford Polyurethane Collection

Base Grade





WO-530  
Bright White



WO-531  
Dove



WO-533  
Bone



WO-539  
Light Grey



WO-532  
Hopfen



WO-535  
Tan



WO-542  
Charcoal



WO-537  
Dark Brown



WO-536  
Saddle



WO-544  
Hunter Green



WO-538  
Chestnut



WO-540  
Burgundy



WO-543  
Blueberry



WO-541  
Espresso



WO-545  
Black



WO-534  
Parchment

# Woodford

## Specifications

- Contents: 100% Polyurethane face with a brushed woven blended polyester backing
- Nominal Total Thickness:  $44 \pm 2$  mils
- Roll Width: 54 inches
- Roll Size: 30 yards
- Weight:  $18.75 \pm 1.25$  ounces per linear yard/54 inches
- Cold Crack:  $-15^{\circ}$  F
- Abrasion Resistance: No significant wear after 200,000 double rubs with #8 cotton duck using the Wyzenbeck test method
- 120 Hrs. WeatherOmeter\*

## Flame Resistance

Manufactured to meet the following flammability\* requirements:

- California Flammability Regulation (Bulletin 117, Section E)
- FMVSS 302
- BIFMA Class A
- UFAC Class 1

\* This term and all corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

## Care and Cleaning Instructions

To prevent build up of dirt and contaminants, which may cause permanent staining, periodic cleaning is highly suggested. The frequency of cleaning is dependent upon the environmental conditions the material is subject to.

### Bleach Cleanable:

When disinfecting with bleach, dilute with water up to 9:1 ratio (10%). Liberally apply diluted disinfectant using a sponge and rinse with cold water. Federal regulations require that guidelines on the bleach label need to be followed for antiseptic or antimicrobial purposes.

### For Normal Use:

Most stains can be easily cleaned using warm soapy water or commercially available non-abrasive detergent solutions like Formula 409® and clear water rinses. Always test cleaner in inconspicuous area first. Moderate scrubbing with a medium bristle brush will help dislodge soiling materials from the depressions of embossed surfaces. Repeat as needed.

## Recommended Applications

- Corporate
- Educational
- Healthcare
- Hospitality
- Marine Interior
- Residential Seating
- RV Seating and Trim

**Note:** This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but it is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.