
## Dillon



## Dillon





## **Dillon**

Content: 100% Polyurethane

Backing: 70% Polyester, 30% Cotton

Finish: Antimicrobial - silver based ion technology

Weight: 20.3 oz. per linear yard

Width: 54"

Environmental Benefit: PVC Free

Phthalate - compliant CPSC sec. 108 Lead - compliant CPSC sec. 101

Abrasion: Heavy Duty - Exceeds 200,000 Cycles

(Wyzenbeek - #8 Cotton Duck Abradant) (ASTM D4157)

Light Fastness: Class 4/200 hrs. min. (AATCC16A)

Color Fastness: Class 5 (ASTM D3597, AATCC 8) Wet

Class 5 (ASTM D3597, AATCC 8) Dry

Physical Properties: Class 5 (ASTM D3511) Brush Pill

130 lbs. warp, 120 lbs. weft (ASTM D5034) Breaking Strength 61 lbs. warp, 81 lbs. weft (ASTM D4034) Seam Slippage

Pass (CFFA 6a) Cold Crack Pass (ISO 1419) 5 weeks

Passes: California Tech. Bulletin #117-2013

UFAC Class I NFPA 260 Class I MVSS 302 Pass IMO A. 652(16) 8.2

Cleanability: WS - Both water and solvent based solutions.

This fabric is made in China.

For samples or further information, please contact:

Culp, Inc.

Contract Fabrics

1823 Eastchester Drive High Point, NC 27265 Phone: (336)-889-5161

Fax: (336)-899-7848

www.culpcontract.com