## Dillon



**BASE GRADE** 





## Dillon

Content:

100% Polyurethane

Backing:

70% Polyester, 30% Cotton

Finish:

Antimicrobial - silver based ion technology

Weight:

20.32 oz.per linear yard

Width:

54"

Environmental Benefit:

**PVC Free** 

Phthalate - compliant CPSC sec. 108 Lead - compliant - CPSC sec. 101

Abrasion:

Heavy Duty-Exceeds 200,000 Cucles

(Wyzenbeek - #8 Cotton duck Abradant) (ASTM 4157)

Light Fastness:

Class 4/100 hrs. min. (AATCC16A)

Color Fastness:

Class 5 (ASTM D 3597,AATCC 8) wet

Class 5 (ASTM D 3597, AATCC 8) dry

Physical Properties:

Class 5 (ASTM D - 3511) Brush Pill

130 lbs. warp, 120 lbs. weft (ASTM D 4034) Breaking Strenght

61 lbs. warp, 81 lbs. weft (ASTM D 4034) Seam Slippage

Passes:

California Tech. Bulletin #117 - 2013

UFAC Class I NFPA 260 Class I MVSS 302 Pass

Cleanability:

WS - Both water and solvent based solutions.

This fabric is made in China.

For samples or further information, please contact:

Culp, Inc.

Contract Fabrics 1823 Eastchester Driv High Point, NC 27265 Phone: (336)-889-5161

Fax: (336)-899-7848 www.culpcontracr.com



12-1-2015