





RT LONDON

Base Grade Patterns

Bangle, Expo, Insight, Origin, Perk

Grade 1 Patterns

Fuse, Syntax

Grade 2 Patterns

Habit





Width - Pattern	Fiber Content & Backing	Finish	Abrasion (D.R.)	Light- fastness	Approx. Repeats	Cleaning Code
54" BANGLE	58% Post Consumer Recycled Polyester, 42% Polyester Acrylic Backing	Soil & Stain Resistant	51,000	(Cl. 4.5) 40 Hrs.		WS
54" <mark>EXPO</mark> 必	65% Post Industrial Recycled Polyester, 35% Post Consumer Recycled Polyester Acrylic Backing	Soil & Stain Resistant	102,000	(Cl. 4) 60 Hrs.	I/8" L, I/8" W	WS
54" <mark>FUSE</mark> ル ▲ 業 ② ☆ *	65% Post Industrial Recycled Polyester, 35% Post Consumer Recycled Polyester Latex Backing	Soil & Stain Resistant	100,000	(Cl. 4.5) 40 Hrs.		WS
54" HABIT	100% Post Consumer Recycled Polyester Acrylic Backing	Soil & Stain Resistant	50,000	(Cl. 4.5) 40 Hrs.	I 5/8" L, 3" W	WS
54" INSIGHT 4. 公. **. 4. *	100% Polyester Acrylic Backing	Soil & Stain Resistant	192,000	(Cl. 5) 40 Hrs.	1/4" L, 1/2" W	WS
58" ORIGIN (A)	100% Polyester Acrylic Backing	Soil & Stain Resistant	282,000	(Cl. 4) 40 Hrs.		WS
54" PERK ℳ	100% Polyester Acrylic Backing	Soil & Stain Resistant	102,000	(Cl. 5) 40 Hrs.	1/4" L, 1/4" W	WS
54" SYNTAX (4)	50% Post Consumer Recycled Polyester, 50% Polyester Acrylic Backing	Soil & Stain Resistant	115,000	(Cl. 4.5) 40 Hrs.	6 I/4" L, 7 I/8" W	WS

*ACT® Registered Certification Marks
These fabrics when used with proper components are compatible with California Technical Bulletin 133.



GREENGUARD Gold Certified. CA Section 01350 compliant. Eligible for CHPS Low-Emitting Material Credits.



08999474

800-366-6839 memosamples.com