Brisa® | Original




RT LONDON

GRADE 5

Acoustical Breathable Custom

Brisa® | Original



533-1359 Strawberry



533-5747 White



533-3277 Moon



533-3276 Wishbone



533-3275 Gravel



533-5802 Ash



533-3866 French Vanilla



533-3019 Birch



533-3822 Bone



533-3946 New Sand



533-3915 Putty



533-3863 Cream




533-3864 Desert Clay



533-3233 Honeycomb



533-3867 Golden



533-3051 Ginger



533-3823 Aztec



533-8202 Koi



533-8245 Cinnabar



533-3591 Caramel



533-3200 Peat



533-8203 Flamingo




533-1359 Strawberry



533-1383 Pompeiian Red



533-1373 Salsa



533-3825 Canyon



533-1344 Rose Red



533-1361 Beet Root



533-9374 Blossom



533-9400 Cabernet



533-9378 Abyss



533-3914 Bark



533-3022 Shiitake



533-3913 Truffle



533-3023 Coffee Bean




533-9310 Hazy Lilac



533-5820 Quicksilver


533-3234 Cookie Dough


303-4510 Celery


533-4487 Sage



533-4488 Olive



533-2698 Sterling Blue



533-2697 Mineral



533-4448 Apple Green


533-4302 Esmeralda



533-4303 Seaweed


533-3272 Iceberg


533-2523 Turq



533-2696 Skyway


533-2645 Cambridge Blue


533-2621 Blue Sea


533-5703 Wrought Iron


533-2694 Night Navy


533-2620 Evening Blue


533-2683 Indigo


533-5749 Black Onyx


Acoustical


Breathable


Custom

Brisa® | Original

General Specifications

Composition:
100% Polycarbonate Polyurethane Surface
65% Polyester, 35% Rayon Backing

Weight:
Approx. 9.3 oz. Per Square Yard
Approx. 315 Grams Per Square Metre

Thickness:
Approx. 1.0 Millimetres

Width:
54 Inches / 137 Centimetres

Performance

Abrasion:
ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*
BS 2543 / 160,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:
14+ Weeks
ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:
ASTM D751

Tear Strength:
ASTM D2261

Breaking Strength:
ASTM D5034

Air Permeability:
ASTM D737

Sound Absorption:
ASTM C423

Colorfastness

Light Fastness:
AATCC 16.3, 200 Hours, Grade 4-5

Crocking:
AATCC 8, Class 5 Wet & Dry

Flammability

F/R Rating:
- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

Other Tests*:
- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under these fire test conditions.

Earth Friendly

- **GREENGUARD Certified**
  - Meets stringent chemical emission limits for various VOCs (ex. Formaldehyde)
  - Promotes healthier indoor air quality
  - Contributes towards satisfying credits under LEED® and BIFMA
- Compliant with Prop 65
- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

For more information on our fabrics, cleaning and care instructions, please visit our website.

GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UL 2818

ultrafabricsinc.com

Ultrafabrics® and logo, and Brisa® are trademarks of Ultrafabrics Inc. Made in Japan.
11/17

Ultrafabrics®